


Hot Water • Propane/Natural Gas Fired Direct/Belt Drive • Electric Motor

Designed as a low maintenance heavy duty pressure washer that's easy on the environment.



- Clean and efficient
- Optional portable - propane models
- Industrial grade components
- 24 volt operating controls for added safety
- Durable polyester powder coat finish for lifelong appearance
- General triplex pump 
- Reliable high efficiency, low emission burner
- Stainless Steel Coil Skin
- Pressure Relief Valve
- Auto Start/Stop/Timer Electronic Ignition (5HP and larger only.)

Model	PSI	GPM	HP	Electrical	Pump	Adj.Temp	BTU's	WT/Lbs	Dimensions
5200	1000	2.0	1.5	115/1/60	Direct Drive	N/A	197,000	400	43"Lx27"Wx41"H
5214	1400	2.1	2.0	115/1/60	Direct Drive	N/A	197,000	400	43"Lx27"Wx41"H
5215	1500	2.8	3.0	230/1/60	Direct Drive	N/A	197,000	400	43"Lx27"Wx41"H
5330	3000	3.0	6.0	230/1/60	Fws3030	N/A	197,000	450	53"Lx27"Wx41"H
5400	2000	3.6	5.0	230/1/60	Belt Drive	STD	345,000	530	53"Lx28"Wx44"H
5403	2000	3.6	5.0	230/460/575/3	Belt Drive	STD	345,000	530	53"Lx28"Wx44"H
5400E6	2300	3.8	6.0	230/1/60	Belt Drive	STD	345,000	530	53"Lx28"Wx44"H
5500	3000	3.9	7.5	230/1/60	Belt Drive	STD	345,000	570	53"Lx28"Wx44"H
5503	3000	3.9	7.5	230/460/575/3	Belt Drive	STD	345,000	530	53"Lx28"Wx44"H
5600	3000	5.0	10.0	230/1/60	Belt Drive	STD	345,000	620	53"Lx28"Wx44"H
5603	3000	5.0	10.0	230/460/575/3	Belt Drive	STD	345,000	550	53"Lx28"Wx44"H

Standard Features:

- Continuous hot water
- Adjustable pressure
- Schedule 80-1/2" Coil (Schedule 40-1/2" 5200 Series)
- 50' foot steel wire braided pressure hose with couplers

- Forged pump head, removable valve caps and ceramic plungers
- Downstream injection applies chemical at low pressure
- Safety high limit
- Insulated trigger controlled gun with safety lock-off and single wand

Options:

- Hour meter
- High pressure soap
- Steam mode 285 °F
- Stainless steel hood/base

Your Local Dealer: