COLD WATER PRESSURE WASHER

Belt Drive • Gasoline Powered • Industrial Cart

 Low Tone Muffler: For guieter operation. Heavy Duty Cart: With powder coated finish.

Separate Unloader:

Diverts water pressure when trigger is not in use. Includes easily adjustable pressure control knob and all brass fittings.

- Honda GX690 Gasoline Engine: Includes electric start, low oil alert system and hour meter.
- Inlet Filter: Helps reduce contaminants from entering the pump.
- Protective Battery Box: Water resistant plastic box for extra protection against weathering. (Battery Not Included.)



• 13" Pneumatic Tires: Ball bearing construction with a steel rim and hub assembly.

Other Features:

 Built In Pressure Gauge Lance and Gun Holder

- Quality Gun and Stainless **Steel Lance Combination:** Easy pull trigger with 48" high pressure lance.
- 50' High Pressure Hose: Durable non-marking steel braided hose.
- Belt Drive: Slower speed increases the life of the pump.
- High Quality Triplex Plunger Pump: All Dynablast pressure washers include GP/Interpump pumps with solid ceramic plungers, thermal pump protector and limited 5 year warranty.
- Rubber Foot: Reduces vibration.
- Large Removable Gasoline Tank: Holds up to 6.6 US Gallons or 25 liters.

SPECIFICATIONS	ASSEMBLED IN CANADA
MODEL	C5050BG
Operating Pressure (PSI):	5000
Volume (GPM):	5
Engine (CC):	690
Pump Speed (RPM):	1845
Dimensions - (LxWxH):	43"x25"x39"

Features and specifications subject to change without prior notice.

SPECIFICATIONS	ASSEMBLED IN CANADA
MODEL	C5050BG
Operating Pressure (PSI):	5000
Volume (GPM):	5
Engine (CC):	690
Pump Speed (RPM):	1845
Dimensions - (LxWxH):	43"x25"x39"
Unit Weight:	314 lbs

INCORPORATED

HPW Incorporated 201 Spinnaker Way, Unit #13, Concord, Ont. Phone: 905 - 761 - 8822 Email: sales1@hpwincorporated.com

Distributed by: