

**LANDA**<sup>®</sup>  
PRESSURE WASHERS

Since 1969

North America's **LARGEST** Manufacturer  
of Industrial **PRESSURE WASHERS**

# HOT

Portable, Electric-Powered,  
Diesel-Heated, Hot Water Pressure Washer

- Up to 3.5 GPM, 2000 PSI
- Belt-Drive Pump with 5-Year Warranty
- Sch. 80 Heating Coil
- 120V, 208V, 230V
- True Steam Model



▲ Heavy-duty **Motor** and cast-iron, bushing **Pulleys** use a convenient 2-bolt pulley adjustment for easy maintenance and longer life; a "V" cogged belt connects the motor to the **High-Pressure Pump**, which features three ceramic plungers and a forged brass head with five-year warranty.

■ High-efficiency **Burner** is protected by a cover and mounted on the end for easy access.

■ Conveniently located **Control Panel** with 3-position switch is housed in a water-resistant electrical box; anti-syphon detergent valve is optional.

■ 36 ft. of high-grade **Electrical Cord** with Ground Fault Circuit Interrupter on all models for operator safety.

■ 50 ft. of steel-wire braid **High Pressure Hose** with 24-inch guard for burst protection.


■ Unique, slide-out **Service Platform** allows for easy access and servicing of pump and unloader.

■ High-heat aluminized steel inner wrap surrounds cold-rolled **Heating Coil** made of Schedule 80 steel pipe with five-year warranty.

■ Unique design allows access to the **Coil Wrap** within minutes by simply removing six bolts.

■ Helpful **Tri-Lingual Labels** with operating instructions in English, Spanish and French for added liability protection and operator convenience.

■ Quick-couple **Nozzle** is made of hardened stainless steel and mounted for ready access.



▲ Optional, E-Zee **Hose Reel** with compact, easy-wind design for tangle-free handling of hose.



■ Two-ply, tubed **Pneumatic Tires** make for easy maneuvering in any terrain; safety brake prevents rolling.

■ Many **Safety Features**, including a rupture disk and thermal pump protector to prevent the build up of excessive pressures or heat.

■ Insulated, fatigue-free **Trigger Gun** with chrome-plated, dual-lance **Variable Pressure Wand** make for easy cleaning and adjusting the pressure while washing.

■ Optional rust-free **Float Tank** with stainless steel inlet filter and backflow protection.

■ Easy-to-attach **Detergent Injector** for soap application.

[www.landa.com](http://www.landa.com)



Since 1969

North America's **LARGEST** Manufacturer  
of Industrial **PRESSURE WASHERS**

# HOT

Portable, Electric-Powered,  
Diesel-Heated, Hot Water Pressure Washer

- Up to 3.5 GPM, 2000 PSI
- Belt-Drive Pump with 5-Year Warranty
- Sch. 80 Heating Coil
- 120V, 208V, 230V
- True Steam Model



## WHY CHOOSE LANDA'S HOT

The HOT is the most economical choice of Landa's electric-powered, diesel-heated hot water pressure washers featuring the heat-efficient horizontal coil. It is also the only line among those with a horizontal coil design that has a true steam cleaner, or steamer—the HOT 3-30035D.

**QUALITY:** The HOT boasts many of the same quality components of other Landa hot water pressure washers, including a belt-drive, tri-plunger high-pressure pump with 5-year warranty, Schedule 80 heating coil made of 1/2-inch pipe and a slide-out service platform—a service tech's dream.

**PORTABILITY:** All of the HOT models weigh less than 500 lbs. and are evenly balanced on four leak-free, tubed, pneumatic tires for easy maneuvering in any terrain. Waffle grips on the two steering bars add to the HOT's portability.

**SAFETY:** Certified to the rigid UL-1776 safety standards, the HOT also has many features that make it extremely safe, including motor thermal overload protection, rupture disk attached to the heating coil, thermal pump protector, flow-activated fuel shut-off switch, 24-inch hose guard for burst protection, and Ground Fault Circuit Interrupter on all models.

## HOT Specifications

Part No.	GPM	PSI	Motor HP	Electrical	Amps	Pump	RPM	Temperature	L x W x H	SHIP WT.
HOT2-11021D	2.0	1000	1.5	120V 1 ph	18	General	1450	Up to 200°F	48" x 29" x 36.5"	485 lbs.
HOT2-15021D	1.9	1500	2	120V 1 ph	20	General	1450	Up to 200°F	48" x 29" x 36.5"	495 lbs.
HOT3-11021D	2.8	1000	2	120V 1 ph	20	General	1750	Up to 200°F	48" x 29" x 36.5"	505 lbs.
HOT4-20021A	3.5	2000	5	230V 1 ph	25	General	1460	Up to 200°F	48" x 29" x 36.5"	530 lbs.
HOT4-20021G	3.5	2000	5	208V 1 ph	27	General	1460	Up to 200°F	48" x 29" x 36.5"	530 lbs.
HOT3-30035D Steamer	2.5	300	1.5	120V 1 ph	12	AR	1250	310°F	48" x 29" x 36.5"	445 lbs.



Distributed by:

## OPTIONS:

Part No.	Description
30-410	Tire upgrade to Mag Wheels (Set of 4)
30-510	Float Tank and Inlet Detergent Metering Valve (All but 4-2000)
30-511	Float Tank and Inlet Detergent Metering Valve (4-2000 only)
30-512	Stainless Steel Outer Coil Wrap
4-02755030	E-Zee Hose Reel
30-5022	E-Zee Reel Mounting Kit
See Dealer	Automatic Start / Stop or Time Delay Shutdown are available upon request

[www.landa.com](http://www.landa.com)