

RGF[®] ENVIRONMENTAL GROUP

MODEL WM-LD

RGF's Advanced Wash Water Recycling System For **Light Duty** pressure and steam cleaning users...



The Model WM-LD collects contaminated water from your wash pad, which typically contains...petroleum hydrocarbons (oil, grease, and fuels), heavy metals, solids, cleaning fluids, and detergents. The collected water is processed through the system and automatically delivered to the pressure or steam-cleaner for re-use.

Applications

This WM-LD wash system is intended for vehicle washing applications such as:

- Military bases
- Rental car companies
- Truck & tractor repair shops
- Fork lift repair shops
- Engine repair shops
- Machinery companies
- Municipal and state garages
- Auto repair shops
- Marine yards
- Equipment rental companies
- City / County transportation
- Fabrication shops

Advantages

- RGF is the Recognized Leader with thousand of systems installed world wide since 1985.
- RGF has the best warranty in the business.
- Zero Discharge Closed Loop System encouraged by the E.P.A.
- No sewer connection required. No NPDES Permits needed.
- Totally Non-ferrous - no rust or corrosion.
- Our unique Catalytic Oxidation Process eliminates the use of chlorine or floccing chemicals for odor control.
- Installation, Maintenance and operation manual included.
- Components are color impregnated & UV protected to eliminate maintenance painting.
- Pre-Wired, Fully Automatic, Easy to Use and Versatile.
- Over 1,100 sq. ft. of polypropylene inclined plate coalescing area and over 2,400 coalescing matrixes.
- Low Maintenance.
- Built in Water Management and Wash / Rinse Capabilities.
- UL-508A Panel Shop Certified
- All filters and separators contain an oil & solids purge system to extend filter life and reduce maintenance.

STORAGE TANK



WM-LD SERIES 2 SKID



SERIES 1 TANK



SPECIFICATIONS

DIMENSIONS: SERIES I TANK	2'W X 4'L X 6'H	TUBING	UV PROTECTED PVC & POLY
SERIES II SKID	4'W X 4'L X 7'H	SERIES I TANK	250 GAL. POLY TANK
STORAGE TANK	4'W X 4'L X 6'-8"H	STORAGE TANK	550 GAL. POLY TANK
FLOW RATE	20 GPM	HYDROCARBON ACCUMULATOR	7 GAL. POLY TANK
ELECTRICAL REQUIREMENTS	220V -30 AMP -SINGLE PHASE	INCLINED TUBE COALESCOR	POLY-PRO INCLINED GRID
WEIGHT (APPROX.)	1,200 lbs.	MICRO-MATRIX COALESCOR	POLY INCLINED GRID FILTER
CFC SYSTEM PUMP	1/2 hp CIRCULATION	MULTI-MEDIA FILTER	150 LBS. MIXED MEDIA
PROCESSING PUMP	1 1/2 hp CENTRIFUGAL	AUTO OIL SKIMMER	PVC ADJUSTABLE
CHEMICAL INJECTION	OXYPUCK SYSTEM	POLISHING FILTER (2)	POLY-PRO HOUSING & 25 M FILTER
VALVES	PVC BALL & ELECTRIC SOLENOID	UV/O3 CATALYTIC CHAMBER	KRYPTON / QUARTZ

RGF Environmental Group

1101 West 13th Street Riviera Beach, Florida 33404
 800 842-7771 Fax 561 848-9454 www.rgf.com