Commercial Vacuums Models 100002, 100005, 100006

Commercial Workhorses

Three choices that will tackle the toughest vacuuming jobs!

Model 100002

• Floor Mount

- Two Heavy Duty Motors Deliver <u>maximum</u> cleaning power and reliable performance.
- High Capacity Filter System Reduces maintenance intervals, saves you money.
- Perform Routine Filter Changes and Maintenance Quickly – Reduces operating costs and labor.
- Large Bore Hose With Anti-Clog Inlet Design –

Keeps your vacuums running profitably.

• Stainless Steel Construction – Stands up to the toughest environments.



Model 100005

- Pole Or Wall Mounting
 - **Two Heavy Duty Motors** Provides greater customer satisfaction with <u>maximum</u> power.
 - High Capacity System Ensures peak airflow and cuts costs and labor.
 - Perform Routine Filter Changes and Maintenance Quickly – Prolong the life of your investment wit easy access.
 - Large Bore Hose With Anti-Clog Inlet Design –

Less machine down time because of trapped debris.

 Stainless Steel Construction – Sturdy design weathers the elements



Model 100006

- Dual Hose Design With Auto Shut-Off Hangers
 - Three Heavy Duty Motors Deliver <u>multi-user</u> cleaning power and reliable performance.
 - High Capacity Filter System Machine can run for longer periods, saves money.
 - Perform Routing Filter Changes and Maintenance
 Quickly –

Less machine down time keeps profits flowing.

- Stainless Steel Construction Strong durability, easy maintenance.
- **On/Off Toggle Switch** Pre-wired for easy installation.





800.968.8227 Visit us at www.IVS-Vacuum.com

Commercial Vacuums Models 100002, 100005, 100006

Commercial Workhorses Three choices that will tackle the toughest vacuuming jobs!

Production Specifications (standard equipment):

Airflow –

(100002, 100005) 150 cu.ft/min., 84" suction lift. (100006) 220 net cu. ft./min., 84" suction lift.

Motors –

(100002, 100005) Two 900 Watt electric, by-pass cooled 7 amps each.

(100006) Three 900 Watt electric, by-pass cooled 7 amps each.

Filters -

(100002, 100005, 100006) Four bag system uses high performance napped synthetic filtration material, 15 sq. ft. effective filtration area and easy access filter service door.

Hose -

(100002, 100005) 2" diameter x 15' long, high flex crushable plastic, includes cuff and polyethylene hand tool. (100006) Two 1-1/2" x 15' hoses.

Hose Hangers –

(100006) Two hose hangers with shut-off adapters.

Tank –

(100002, 100005, 100006) 304 grade, 18 gauge stainless steel, brushed finish. Size: 42" H x 18.5" OD.

Mounting -

(100002, 100006) Three mounting lugs for 1/2" bolts (concealed front bolt).

(100005) Two side-mount brackets for wall or pole mounting.

Dimensions –

(100002) Unit: 52" H x 20" W x 24" D With shipper: 58" H x 25.5" W x 28" D (100005) Unit: 52" H x 26" W x 30" D With shipper: 58" H x 28" W x 28" D (100006) Unit: 52" H x 28" W x 20" D With shipper: 58" H x 28" W x 28" D

Dome Dimensions –

20" (OD) x 10.5" H (stainless steel) 21.5" (OD) x 12" H (polyethylene)

Unit Weight -

(100002) Net 78 lbs; w/shipper 137 lbs (100005) Net 86 lbs; w/shipper 141 lbs (100006) Net 92 lbs; w/shipper 137 lbs

More Commercial Vacuum Features:

- Quiet Kit Options: Sound attenuating insulation and/or special quiet motors available. Ideal for indoor applications.
- Finish Options: Maintenance-free mirror finish.
- Motor and Power Options:

Available for use with 120 VAC or 240 50/60 hz VAC power. Three motors are available for premium power marketing or high altitude installations.

- Switch and Timer Options: On/off toggle or with push-button programmable timer.
- Dome Options: Stainless Steel standard, Poly domes av

Stainless Steel standard. Poly domes available in five color choices, lighted or unlighted.

• Hose Options:

Hose choices include 1-1/2" or 2" diameter in five colors. Available in 15', 25', and 50' lengths. Exclusive tapered hose provides clog-free, high-flow power

(15 foot, gray only).



INDUSTRIAL VACUUM SYSTEMS

3611 3 Mile Rd. NW • Grand Rapids, MI 49534 800.968.8227 • Fax: 616.246.1706 www.IVS-Vacuum.com