

# DET SERIES

## COLD WATER PRESSURE WASHER

Direct Drive • Electric Powered • Industrial Cart

- **Downstream Adjustable Chemical Injector:**  
For low pressure soap and chemical injection.
- **Quick Connect Hose Connectors:**  
For easy on/off connections and tangle free hoses.
- **Baldor TEFC Motor:**  
Low speed induction motor extends the life of your pump.
- **Separate Unloader with Pressure Switch:**  
Diverts water pressure when trigger is not in use. Includes easily adjustable pressure control knob and all brass fittings.
- **Inlet Filter:**  
Helps reduce contaminants from entering the pump.
- **Time Delay Shutdown:**  
Extends the life of your Pressure Washer.

- **Heavy Duty Cart:**  
Includes gun and lance holder.  
With Powder Coated Finish.

- **Four Quick Connect Nozzles:**  
Colour coded nozzles included are 0°, 15°, 25° and soap mounted on lance.

- **50' High Pressure Hose:**  
Durable non-marking steel braided hose.

- **Quality Gun and Stainless Steel Lance Combination:**  
Easy pull trigger with 48" lance.

- **High Quality Triplex Plunger Pump:**  
All Dynablast pressure washers include GP/Interpump pumps with solid ceramic plungers, thermal pump protector and limited 5 year warranty.

- **Rubber Foot:**  
Reduces vibration.

- **16" Pneumatic Tires**  
Ball bearing construction with a steel hub assembly.

OPTIONAL  
HOSE KIT (HR3KIT)  
AVAILABLE



C4030DET

### Other Features:

- CSA Approved
- Heavy Duty Power Cord and Plug
- Pressure Gauge

### SPECIFICATIONS

ASSEMBLED IN CANADA

MODEL	C4030DET
Operating Pressure (PSI):	3000
Volume (GPM):	4.0
Motor (HP):	7.5
Pump Speed (RPM):	1750
Available Voltage (1 Phase):	230
Amps:	33
Wheel Size:	16"
Unit Dimensions (LxWxH):	41"x31"x24"
Unit Weight:	270 lbs

Features and specifications subject to change without prior notice.

# Dynablast®



# HPW INCORPORATED

201 Spinnaker Way, Unit #13, Concord, Ont.  
P:905-761-8822 E:sales1@hpwincorporated.com

www.dynablast.com



DET-F-06/11